

MIDLAND COUNTY ROAD COMMISSION

BID FORM

Sealed Proposals will be received at the office of the Board of Road Commissioners, County of Midland, at 2334 N. Meridian Road, Sanford, Michigan 48657 until:

DATE: Friday, March 3, 2017, at 9:00 a.m.

Item No. 26 – Concrete Blocks

<u>PAY ITEM</u>	<u>PRICE PER UNIT</u>
Split Face Concrete Masonry Block	\$_____/Each
Solid Concrete Masonry Block	\$_____/Each
Standard 8" Hollow Core Concrete Masonry Block	\$_____/Each
4"x8"x16" Solid Concrete Masonry Block	\$_____/Each
Interlocking __x2'x2' Concrete Masonry Block	2.5' Long----- \$_____/Each
	3' Long----- \$_____/Each
	4' Long----- \$_____/Each
	5' Long----- \$_____/Each
	6' Long----- \$_____/Each
	4' Long Corner \$_____/Each
	5' Long Corner \$_____/Each
6' Long Corner \$_____/Each	

Materials

Split Face Concrete Masonry Block shall consist of furnishing split face hollow core concrete masonry units (cmu) meeting ASTM c90 with the modifications that the block shall have a minimum compressive strength of 4000 psi and a maximum absorption rate of 6.5%.

Solid Concrete Masonry Block shall consist of furnishing solid concrete masonry units (cmu) meeting ASTM c90 with the modifications that the block shall have a minimum compressive strength of 4000 psi and a maximum absorption rate of 6.5%.

Standard 8" Hollow Core Concrete Masonry Block shall consist of furnishing cmu's meeting ASTM c90 loadbearing normal weight requirements.

Interlocking Concrete Masonry Blocks shall consist of furnishing solid concrete masonry units cast with minimum 3500 psi compressive strength concrete. Blocks must be true to dimension within ¼ inch in 4 feet, have minimum 3” deep “V” style lock, and a single lifting point.

Include in Price Per Unit Delivery of all items to:

Midland County Road Commission
2334 N Meridian Road
Sanford, MI 48657

COMPANY BIDDING _____

CONTACT PERSON _____

ADDRESS _____

PHONE/FAX _____

AUTHORIZED SIGNATURE TITLE

INDICATE ON ENVELOPE: Company Name, Item Number, Bid Item, Time and Date